AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A double wrapper cigarette <u>having a triple layer structure</u>, comprising:

a rod-shaped filler including a tobacco material,

an inner wrapper wrapped around said rod-shaped filler without overlap of opposite side edges thereof,

an outer wrapper surrounding said inner wrapper, said outer wrapper including overlap of opposite side edges thereof, and

a perfume emitting layer provided between said inner wrapper and said outer wrapper thereby forming the cigarette having the triple layer structure,

wherein said perfume emitting layer covers an entire outer circumferential surface of said inner wrapper, and includes a perfume material for weakening odor of sidestream smoke of the cigarette and glue for carrying the perfume material.

- 2. (Original) The double wrapper cigarette according to claim 1, wherein said inner wrapper and said outer wrapper include an additive for reducing the sidestream smoke.
 - 3. (Cancelled)
- 4. (Previously Presented) The double wrapper cigarette according to claim 1, wherein the glue is polyvinyl acetate glue.

Docket No. 1131-0500P

Application No. 10/771,328
Reply dated August 14, 2007

Reply to Office Action of April 19, 2007

Art Unit: 1731
Page 3 of 12

5. (Previously Presented) The double wrapper cigarette according to claim 1, wherein

the perfume material is in powder form or in grain form.

6. (Currently Amended) A manufacturing machine for manufacturing a double

wrapper cigarette having a triple layer structure, the double wrapper cigarette including a

rod-shaped filler including a tobacco material, an inner wrapper wrapped around said rod-

shaped filler without overlap of opposite side edges thereof, an outer wrapper surrounding

said inner wrapper, said outer wrapper including overlap of opposite side edges thereof, and

a perfume emitting layer provided between said inner wrapper and said outer wrapper,

the manufacturing machine comprising:

a first feeding path along which an inner web is fed for obtaining the inner wrapper,

a second feeding path along which an outer web is fed for obtaining the outer

wrapper,

a wrapping section for continuously forming a tobacco rod by receiving the inner and

outer webs from said first and second feeding paths, laying the inner web on the outer web to

thereby form a double web, receiving the tobacco material on the double web, and wrapping

the double web around the tobacco material to form the rod-shaped filler,

a cutting section for cutting the tobacco rod formed at said wrapping section into

pieces of a predetermined length of the double wrapper cigarette, and

at least one perfume material supply device located along one of said first and second

Docket No. 1131-0500P

Application No. 10/771,328

Reply dated August 14, 2007

Reply to Office Action of April 19, 2007

Page 4 of 12

Art Unit: 1731

feeding paths,

said perfume material supply device being so provided as to apply material including

a perfume material for weakening odor of sidestream smoke of the cigarette onto at least one

of the inner and outer webs fed along said first and second feeding paths in the form of a

layer, to thereby form the triple layer structure, with the perfume emitting layer disposed

between the inner and outer webs of the double web,

wherein said perfume emitting layer covers an entire outer circumferential surface of

said inner wrapper, and includes the perfume material and glue for carrying the perfume

material.

7. (Original) The manufacturing machine according to claim 6, wherein said

perfume material supply device includes

a nozzle type applicator for applying a perfume emitting liquid including the perfume

material onto the inner web or the outer web.

8. (Original) The manufacturing machine according to claim 6, wherein said

perfume material supply device includes

a glue applicator for applying glue onto the inner web or the outer web to thereby

make an adhesive surface, and

a diffuser for diffusing a perfume emitting material in powder or grain form over the

adhesive surface of the inner web or the outer web.

Docket No. 1131-0500P

Application No. 10/771,328
Reply dated August 14, 2007

Reply to Office Action of April 19, 2007

Art Unit: 1731
Page 5 of 12

9. (Original) The manufacturing machine according to claim 8, wherein said diffuser

includes

a first brush roller rotatably located under said feeding path, for blowing up the

perfume emitting material toward said adhesive surface of the inner web or the outer web,

and

a second brush roller rotatably located downstream of said first brush roller, for

removing a surplus of the perfume emitting material attached to the adhesive surface.

10. (Currently Amended) A method of manufacturing a double wrapper cigarette

having a triple layer structure, the double wrapper cigarette including a rod-shaped filler

including a tobacco material, an inner wrapper wrapped around said rod-shaped filler without

overlap of opposite side edges thereof, an outer wrapper surrounding said inner wrapper, said

outer wrapper including overlap of opposite side edges thereof, and a perfume emitting layer

provided between said inner wrapper and said outer wrapper thereby forming the cigarette

with the triple layer structure,

the method of manufacturing comprising the steps of:

feeding an inner web and an outer web to a wrapping section of a cigarette

manufacturing machine, and, at an inlet of the wrapping section, laying the inner web on the

outer web to thereby form a double web, the inner wrapper being obtained from the inner

web, and the outer wrapper being obtained from the outer web,

Application No. 10/771,328

Reply dated August 14, 2007

Reply to Office Action of April 19, 2007

Docket No. 1131-0500P Art Unit: 1731

Page 6 of 12

applying material including a perfume material for weakening odor of sidestream

smoke of the cigarette onto at least one of the inner and outer webs thereby forming the

perfume emitting layer while the inner and outer webs are being fed, the perfume emitting

layer being disposed between the inner and outer webs of the double web, and covering an

entire outer circumferential surface of said inner wrapper, and including the perfume material

and glue for carrying the perfume material;

supplying the tobacco material onto the double web at the inlet of the wrapping

section,

forming a tobacco rod continuously by wrapping the double web around the tobacco

material while the double web is passing through the wrapping section together with the

tobacco material, in order to form the rod-shaped filler, and

cutting the tobacco rod into pieces of a predetermined length, thereby forming the

double wrapper cigarette with the triple layer structure.